

Dispersive optomechanics: a membrane inside a cavity

A. M. Jayich¹, J. C. Sankey¹, B. M. Zwickl¹, C. Yang¹, J. D. Thompson¹, S. M. Girvin^{1,2}, A. A. Clerk³, F. Marquardt⁴, J. G. E. Harris^{1,2}

1. Department of Physics, Yale University, New Haven, CT

2. Department of Applied Physics, Yale University, New Haven, CT

3. Department of Physics, McGill University, Montreal, Canada

4. Department of Physics, Arnold-Sommerfeld-Center for Theoretical Physics and Center for Nanoscience, München, Germany

Abstract. We present the results of theoretical and experimental studies of dispersively coupled (or “membrane in the middle”) optomechanical systems. We calculate the linear optical properties of a high finesse cavity containing a thin dielectric membrane. We focus on the cavity’s transmission, reflection, and finesse as a function of the membrane’s position along the cavity axis and as a function of its optical loss. We compare these calculations with measurements and find excellent agreement in cavities with empty-cavity finesse in the range 10^4 - 10^5 . The imaginary part of the membrane’s index of refraction is found to be $\sim 10^{-4}$. We calculate the laser cooling performance of this system, with a particular focus on the less-intuitive regime in which photons “tunnel” through the membrane on a time scale comparable to the membrane’s period of oscillation. Lastly, we present calculations of quantum non-demolition measurements of the membrane’s phonon number in the low signal-to-noise regime where the phonon lifetime is comparable to the QND readout time.

PACS numbers: 40.42, 42.50.-p, 42.50.Wk

1. Introduction

Nearly all the optomechanical systems which have been studied to date consist of an optical cavity whose detuning is proportional to the displacement of some mechanical degree of freedom. The mechanical degree of freedom is most commonly the position of the end mirror of a Fabry-Perot cavity [1–14] or the elongation of a waveguide [15–18]. In these systems the radiation pressure has a physically intuitive form: it is a force which acts on the mechanical degree of freedom and is proportional to the instantaneous intracavity optical power.

Recently a new type of optomechanical system has been described in which the mechanical degree of freedom is a flexible, partially transparent object (such as a dielectric membrane) placed inside a Fabry-Perot cavity [19–24]. In this type of system the cavity detuning (and hence the radiation pressure) is periodic in the membrane displacement.

Here we analyze several aspects of such a “dispersive” optomechanical device. We calculate its linear optical properties (transmission, reflection, and finesse) as a function of experimentally relevant parameters, and compare these calculations with experiments. We demonstrate a dispersive optomechanical device with a finesse $F = 150,000$, and argue that it should be possible to realize $F = 500,000$ using present-day technology.

We also present calculations of the radiation pressure-induced cooling and heating in these systems. Because dispersive optomechanical systems consist of a compound optical cavity, their laser cooling is more complicated than in the more familiar “reflective” optomechanical devices described, e.g., in refs [1–18]. Lastly, we consider phonon quantum non-demolition (QND) measurements in dispersive optomechanical systems [19, 25]. We focus in particular on phonon QND measurements with low signal-to-noise ratios, and consider how quantum effects might be manifest in such non-ideal experiments.

2. Linear optical properties: calculations

The geometry of the dispersive optomechanical devices considered in this paper is shown in figure 1. Our one-dimensional model consists of two cavity end mirrors with electric field reflectivity r and transmission t (the two cavity mirrors are assumed identical in this paper, but the extension to unequal mirrors is straightforward). The dielectric membrane placed between the two end mirrors has a thickness L_d and index of refraction n . The membrane’s electric field reflectivity r_d and transmission t_d are then given by [26]

$$r_d = \frac{(n^2 - 1) \sin knL_d}{2in \cos knL_d + (n^2 + 1) \sin knL_d} \quad (1)$$

$$t_d = \frac{2n}{2in \cos knL_d + (n^2 + 1) \sin knL_d} \quad (2)$$

where k is the wavenumber of the light incident on the membrane.




Figure 1. Schematic illustration of the dispersive optomechanical system. The membrane is represented as a mass on a pendulum. Enclosing the membrane are the end mirrors that define a high finesse cavity. A_{in} , A_{ref} , A_{tran} , A_1 , A_2 , A_3 , A_4 are the incident, reflected, transmitted and circulating fields.

Note that r_d and t_d are in general complex (reflecting the phase shift acquired by light reflected from or transmitted through a dielectric slab). If n is real, then $|r_d|^2 + |t_d|^2 = 1$. However in general n will be complex, with the imaginary part determining the membrane's optical absorption.

To find the transmission and reflectivity of the cavity as a whole, we solve the following system of equations:

$$A_1 = itA_{in} + rA_2e^{ikL_1} \quad (3a)$$

$$A_2 = r_dA_1e^{ikL_1} + it_dA_4e^{ikL_2} \quad (3b)$$

$$A_3 = it_dA_1e^{ikL_1} + r_dA_4e^{ikL_2} \quad (3c)$$

$$A_4 = rA_3e^{ikL_2} \quad (3d)$$

$$A_{refl} = itA_2e^{ikL_1} + rA_{in} \quad (3e)$$

$$A_{tran} = itA_3e^{ikL_2} \quad (3f)$$

Here A_1 through A_4 are the electric field amplitudes of travelling waves in the cavity (as shown in figure 1), and A_{in} , A_{refl} , and A_{trans} are the amplitudes of the incident, reflected, and transmitted waves. L_1 and L_2 are the lengths of the left- and right-hand halves of the cavity shown in Figure 1 [27].

Since we are primarily interested in cases where the cavity finesse is high and the membrane absorption is low, we find the cavity resonance frequencies by solving for the eigenfrequencies of the closed lossless cavity (i.e., assuming $r = 1$ and $\text{Im}(n) = 0$). The solution gives:

$$\delta_T^{(0)} = 2\phi_r + 2\cos^{-1}(|r_d| \cos \delta) \quad (4)$$

where $\delta_T^{(0)}$ is the cavity's resonance frequency scaled by $2\pi/f_{FSR}$ and f_{FSR} is the cavity's free spectral range. The scaled membrane position is $\delta \equiv 2k\Delta x$. ϕ_r is the complex phase of r_d . From this expression it is clear that the magnitude of the membrane's reflectivity




Figure 2. Cavity detuning as a function of membrane position. The resonant frequencies of three of the cavity's longitudinal modes are plotted (in units of the cavity free spectral range) for several values of the membrane reflectivity. The membrane's power reflectivities $|r_d|^2$ are the following: red: 0.000, orange: 0.080, yellow: 0.450, green: 0.773, blue: 0.982, and black: 0.999. For this calculation the various reflectivities were realized by fixing the membrane thickness and varying the index of refraction.

$|r_d|$ determines the dependence of $\delta_T^{(0)}$ on the membrane position. ϕ_r , the complex phase of r_d , sets an overall offset to $\delta_T^{(0)}$.

The cavity detuning versus membrane position is shown for several membrane reflectivities in figure 2. For illustrative purposes the membrane reflectivity was varied by setting the membrane thickness to be unphysically small ($L_d = 0.01$ nm) and varying n .

The analytic expressions for the transmission through the cavity and reflection from the cavity are also straightforward, but are too cumbersome to display here. We have not found a simple expression for the cavity finesse; instead we estimate it numerically from the linewidth of the transmission resonances.

Figure 3 shows the finesse, resonant transmission (i.e., the transmission when the laser is resonant with the cavity), and the resonant reflection as a function of membrane position. These plots assume $L_d = 50$ nm, $\frac{2\pi}{k} = 1064$ nm, $r = 0.99991$ and $t = 5.28 \times 10^{-3}$ (i.e., the power transmission of each end mirror is 16% of what it would be if it were lossless) corresponding to an empty-cavity finesse of 18,000. In each plot the blue curve corresponds to $n = 2.2$ (i.e., a lossless membrane), while the red curve corresponds to $n = 2.2 + 1.5 \times 10^{-4}i$ (i.e., a membrane with some optical loss).

The differences between the curves for the lossless membrane (blue) and the lossy membrane (red) can be understood qualitatively. Placing a lossless membrane inside a cavity does not alter the rate at which photons leak out of the cavity; as a result the blue curve in figure 3(a) is flat. However the position of a lossless membrane does modulate the resonant transmission (figure 3(b)) because the cavity eigenmodes will be modified by the membrane. Cavity modes primarily localized on the right-hand side




Figure 3. Calculated finesse (a), resonant transmission (b), and resonant reflection (c) of the dispersive optomechanical cavity as a function of membrane position. The blue curves correspond to a lossless membrane, while the red curves correspond to a lossy membrane. Note that all the calculations assume the same (non-zero) loss in the end mirrors. This leads to a reflection and transmission which do not add to unity, and which depend differently upon the membrane position. The parameters used in this calculation are given in the text.

of the cavity in figure 1 will leak primarily out of the right-hand mirror, leading to an increased transmission coefficient for the cavity as a whole. Likewise, modes localized predominantly on the left-hand side of the cavity will couple primarily to external modes to the left of the cavity, leading to an increased reflection coefficient (figure 3(c)).

When n is complex, intracavity photons can be lost to the membrane absorption. This additional loss process lowers the cavity finesse by an amount proportional to the overlap of the cavity mode with the membrane, giving rise to the dips in the red curve of figure 3(a) when the membrane is positioned at an antinode of the cavity mode. Note that for the parameters used in this calculation, the finesse is not appreciably reduced from its empty-cavity value if the membrane is placed at a node of the optical field (i.e., corresponding to the peaks in the red curve of figure 3(a)).

The loss of photons due to absorption in the membrane also prevents photons from transiting the cavity. As a result the resonant transmission has pronounced dips when the membrane is at an antinode (red curve in figure 3(b)). The reflection signal (figure 3(c)) arises from interference between intracavity light leaking out through the left-hand end mirror (which is affected by the membrane's absorption) and light promptly reflected from the left-hand end mirror (which is not). As a result its form is less intuitive, with membrane absorption leading to an asymmetric dependence on membrane position.

3. Linear optical properties: measurements

3.1. Experimental Setup

Schematic illustrations of our experiment are shown in figures 4 and 5. Laser light is produced by a Nd:YAG laser (Innolight, Hannover, Germany) with wavelength $\lambda = 1064$ nm. The light passes through an acousto-optic modulator (AOM), and the first-order beam is sent to the optomechanical cavity via the steering mirrors M1 and M2. The cavity is formed by two dielectric mirrors each with a 5 cm radius of curvature (coated by Advanced Thin Films, Longmont, CO, USA). The mirrors are mounted to a cylindrical Invar spacer 6.7 cm long with a hole drilled along its axis to accomodate the cavity mode.

The Invar spacer has a second hole drilled perpendicular to the cavity axis, allowing us to introduce the dielectric membrane into the waist of the cavity mode. The membrane is mounted on two piezoelectric elements. The first allows us to apply high frequency ($\simeq 300$ kHz), small amplitude (~ 1 nm) oscillations to the membrane (e.g., to excite its mechanical eigenmodes). The second piezo allows us to translate the membrane by roughly $2\text{ }\mu\text{m}$ along the cavity axis. The piezo elements are in turn mounted to a tilt stage (Thorlabs, Newton, NJ, USA KM05) which is rigidly attached to the Invar spacer. The tilt stage includes vacuum-compatible motorized actuators (Thorlabs, Newton, NJ, USA Z612V) allowing us to adjust *in situ* the angular alignment of the membrane relative to the cavity axis. In practice we have found that the membrane needs to be aligned to roughly 5 arcseconds in order to achieve the highest finesse described below.




Figure 4. Illustration of the optical cavity. The Invar cavity support (A) is mounted to the inside of the vacuum chamber. A series of alumina spheres (B) are mounted in cone-shaped recesses to provide kinematic mounting between the support and the Invar cavity spacer (C). The end mirrors (D) define the optical cavity. The membrane and piezoelectric elements are mounted to the Invar arm (E) which is in turn mounted to the tilt stage (F). The tilt stage can be adjusted *in situ* by two motorized actuators (G).

The membrane used in these experiments is a commercial, 50 nm thick, 1 mm $\times$ 1 mm SiN x-ray window (Norcada, Edmonton, AB, Canada). The membrane is supported by a 200 μ m thick Si frame. The exceptional mechanical properties of these membranes have been described elsewhere [28].

In practice we first align the cavity with the membrane removed. Then the membrane is inserted and its tilt and transverse position are adjusted until good transmission through the cavity is achieved.

For most of the measurements presented here, the cavity is mounted inside a vacuum chamber which is pumped down to $\sim 10^{-6}$ torr by an ion pump. Good vacuum is crucial to maintaining the membrane's high mechanical quality factor.

3.2. Measurements

We monitor the optical power reflected from and transmitted through the cavity using the photodiodes shown in figure 5. We can also determine the transverse profile of the cavity mode by imaging the transmitted beam with a video camera.

Figure 6(a) shows the optical power transmitted through the cavity as a function of the laser frequency and the membrane position when the laser is mode-matched to the




Figure 5. A schematic of the experimental setup. The membrane is depicted in grey between the two high finesse cavity end mirrors. The transmission and reflection are monitored with photodetectors (PD) and the signals are sent to a data acquisition (DAQ) card.

cavity's $\text{TEM}_{0,0}$ modes. The dark bands (indicating high transmission) correspond to the cavity's resonant frequencies. Comparison of these resonant bands with (4) gives a value of $|r_c| = 0.35$. As with all the data in this paper, the calibration of the membrane position is taken from the assumption that the features in the data are periodic in the membrane displacement with period π/k .

Figure 6(b) shows similar data, but taken with the input beam aligned in such a way as to couple to the $\text{TEM}_{0,0}$ mode and the nominally degenerate doublet consisting of the $\text{TEM}_{0,1}$ and $\text{TEM}_{1,0}$ modes [29]. In figure 6(c), the input is realigned to couple into still more of the cavity's modes. The cavity spectra shown in these figures can be easily explained using the standard description of higher-order transverse modes in optical cavities [30], and a detailed description will be given in a future publication.

The cavity finesse is determined from cavity ringdown measurements. In these, the laser frequency is swept slowly while the optical power transmitted through the cavity is monitored. When the transmitted signal exceeds a pre-determined threshold (indicating that the laser is coming into resonance with the cavity) the AOM switches off the input beam and the transient leakage of light out of the cavity is monitored. This decay has a single exponential form [19, 28] whose time constant, τ , is related to the cavity finesse, F , via $F = 2\pi f_{FSR}\tau$. Figure 7(a) shows the finesse of the cavity's $\text{TEM}_{0,0}$ mode as a




Figure 6. Measured transmission (on a linear scale) as a function of laser frequency (in units of the cavity free spectral range) and the membrane position. In (a) the input beam is coupled almost exclusively to the cavity's TEM_{00} (transverse Gaussian) mode. In (b) the input beam is coupled to both the TEM_{00} and the $\text{TEM}_{m+n=1}$ transverse modes. In (c) the input beam is coupled to several transverse modes, including the Gaussian.

function of membrane position. The solid line in figure 7(a) is a fit to the calculation described above and shown in figure 3(a).

Figures 7(b) and (c) show the cavity transmission and reflection on the $\text{TEM}_{0,0}$ resonance as a function of the membrane position. The solid lines are fits to the data using the calculations described above. The data in Figure 7 were taken with the device in vacuum.

The fits in figure 7 assume $L_d = 50$ nm, that the empty cavity finesse is 16,500, and that the end mirrors' transmission and reflection coefficients are $t = 5.52 \times 10^{-3}$,




Figure 7. Measurements and fits of the cavity's finesse (a), resonant transmission (b), and resonant reflection (c) as a function of membrane position. The solid curves are fits to the data. These fits assume an empty-cavity finesse of 16,500 and give an imaginary part of the membrane's index of refraction of 1.5×10^{-4} .

and $r = 0.99991$ (consistent with measurements of the cavity when the membrane was removed). Given these constraints, the fits yield $n = 2.2 + 1.5 \times 10^{-4}i$. The agreement between the data and fits indicates that our simple model does a reasonable job of describing the system. The few anomalous data points in figures 7(a), (b) and (c) correspond to membrane positions in which the $\text{TEM}_{0,0}$ mode becomes degenerate with other cavity modes (see, e.g., figure 6(c)). Such degeneracies are not accounted for in our simple one-dimensional model.

3.3. Discussion

The loss in the membrane places limits on the maximum obtainable finesse. However the data in figure 7(a) indicates that this limit depends strongly upon where the membrane is placed relative to the cavity nodes and antinodes. In order to determine this limit quantitatively, we use the value of $\text{Im}(n) = (1.5 \pm 0.1) \times 10^{-4}$ extracted from the data and fits in figure 7(a) to calculate the finesse of hypothetical devices which are identical to the ones measured here but with higher reflectivity end mirrors. The result is shown in figure 8, and indicates that for experiments in which the membrane can be placed at a node, it should be possible to achieve $F \simeq 500,000$ with state-of-the-art end mirrors (i.e., those corresponding to an empty-cavity finesse of 1,000,000). For experiments in which the membrane must be placed away from a node, figure 7 (a) indicates that the optical loss in these membranes cannot be compensated for by better end mirrors.

To test the prediction shown in figure 8 we replaced the end mirrors used in the measurements described above with end mirrors giving a measured empty-cavity finesse $205,000 \pm 10,000$. Figure 9 shows the resulting finesse (measured in air) as a function of membrane position, along with a fit which gives $\text{Im}(n) = (2.3 \pm 0.06) \times 10^{-4}$ (the empty cavity finesse is set to 205,000). Although these fits indicate that there may be some sample-to-sample variation in the membranes' absorption, the overall level of agreement between the four sets of data (in figures 7 and 9) and the theory indicates that extrapolation to still higher-reflectivity end mirrors is justified, and that it should be possible to realize a dispersive optomechanical system with a cavity finesse $\approx 500,000$ (see figure 8). We have assumed $L_d = 50$ nm throughout this discussion; still higher finesse could be achieved with thinner membranes, albeit with a decrease in optomechanical coupling.

This high finesse is realized when the membrane is positioned at a node of the intracavity field. This arrangement is ideal for the phonon QND measurements described in [19] and below. However it also corresponds to a point at which the adiabatic radiation pressure is identically zero, and so may seem to preclude the realization of more familiar optomechanical effects such as laser cooling. In fact the situation is somewhat more complicated, as described in the following section.




Figure 8. A plot of the calculated finesse as a function of membrane position for different cavity end mirrors. All three curves assume the membrane's index of refraction is $n = 2.15 + 1.5 \times 10^{-4}i$. The empty cavity finesse is taken to be 100,000 (lowest curve), 314,000 (middle curve), and 1,000,000 (uppermost curve). When the membrane is positioned at a node, the device's finesse can be $> 500,000$.




Figure 9. Finesse as a function of membrane position in a higher-finesse cavity. Similar to figure 3 (a), but taken with end mirrors giving an empty cavity finesse $\approx 205,000$. The fit assumes an empty cavity finesse of 205,000 and gives $\text{Im}(n) = 2.3 \times 10^{-4}$.

4. Optomechanical cooling and heating

In this section, we obtain the optomechanical cooling and heating rates (as well as the optomechanical spring effect) in a membrane-in-the-middle (MIM) setup. We do so by solving the linearized coupled classical equations of motion for the membrane coordinate x and the amplitudes $\alpha_{L,R}$ of two optical modes in the left and the right halves of the cavity. This means we are assuming that the membrane reflectivity $|r_c| \rightarrow 1$ (corresponding, e.g. to the black curve in figure 2, and that the left and right half cavities are nearly degenerate (corresponding to membrane positions near the avoided

crossings in figure 2). Although this regime has not been achieved experimentally, it is in this situation that the most striking deviations from the usual (i.e., “reflective”) setup are to be expected and indeed are realized. Note that modeling a device in which $|r_c| \ll 1$ (corresponding to an approximately sinusoidal relationship between $\delta_T^{(0)}$ and Δx) would require including the contributions from many different modes, not just two.

To set the scene, we first review the calculation of the linearized optomechanical dynamics for the simpler, well-understood case of a single cavity mode in a “reflective” optomechanical device [31, 32]. We will present it in a way that prepares us for the derivation involving the “dispersive” optomechanical device.

4.1. Linearized dynamics of standard optomechanical systems

We have the following equations of motion for the membrane coordinate x and the complex light amplitude α (rescaled such that $\alpha = 1$ at resonance, and taken in a frame rotating at the laser frequency ω_L):

$$\dot{\alpha} = i(\Delta - \omega'x)\alpha + \frac{\kappa}{2}(1 - \alpha) \quad (5)$$

$$\ddot{x} = -\omega_M^2(x - x_0) - \Gamma_M\dot{x} + \mathcal{P}|\alpha|^2 \quad (6)$$

Here $\Delta = \omega_L - \omega_{\text{cav}}[x = 0]$ is the frequency detuning of the incoming laser radiation with respect to the optical cavity mode frequency, $\omega' = \partial\omega_{\text{cav}}/\partial x$ is the derivative with respect to the coordinate ($\omega' = -\omega_L/L$ in the usual setup, with L being the cavity length), κ is the cavity’s intensity ringdown-rate, ω_M the membrane’s mechanical frequency, x_0 its equilibrium position in the absence of light, and Γ_M its damping constant. The radiation pressure constant $\mathcal{P}$ introduced here has dimensions of frequency squared, and is given by $\mathcal{P} = -(\omega'/\omega_L)E_{\text{res}}/m$, where m is the membrane’s effective mass and E_{res} is the light energy stored inside the cavity at resonance (proportional to the input intensity, $E_{\text{res}} = 4I_{\text{in}}/\kappa$ for a single-sided cavity).

The steady-state solution $(\bar{x}, \bar{\alpha})$ can be obtained by setting $x(t) = \bar{x}$ and $\alpha(t) = \bar{\alpha}$ and solving the resulting set of nonlinear equations. Note that for strong radiation pressure effects, more than one stable solution appears (two in the case discussed here). This is the static bistability that was found experimentally by Dorsel et al. [33]. We now assume this solution has been found and linearize the equations of motion around it, using $|\alpha|^2 \approx |\bar{\alpha}|^2 + \bar{\alpha}^*\delta\alpha + \text{c.c.}$

$$\delta\dot{\alpha} = -i\omega'(\bar{x}\delta\alpha + \delta x\bar{\alpha}) + i\Delta\delta\alpha - \frac{\kappa}{2}\delta\alpha \quad (7)$$

$$\delta\ddot{x} = -\omega_M^2\delta x - \Gamma_M\dot{\delta x} + \mathcal{P}(\bar{\alpha}^*\delta\alpha + \text{c.c.}) + f(t) \quad (8)$$

Here we have added a test force leading to an acceleration f . The response to this force will reveal the change in the membrane’s damping rate and spring constant brought about by the radiation field. At a given driving frequency ω , we decompose into

positive and negative frequency components: $\delta\alpha(t) = \delta\alpha_- e^{-i\omega t} + \delta\alpha_+ e^{+i\omega t}$, and likewise for δx [where $\delta x_- = \delta x_+^*$ due to $\delta x(t)$ being real-valued]. This leads to

$$\pm i\omega\delta\alpha_{\pm} = -i\omega'(\bar{x}\delta\alpha_{\pm} + \delta x_{\pm}\bar{\alpha}) + i\Delta\delta\alpha_{\pm} - \frac{\kappa}{2}\delta\alpha_{\pm}, \quad (9)$$

and therefore $\delta\alpha_{\pm} = \chi_{\alpha}(\pm\omega)\delta x_{\pm}$, with the susceptibility χ_{α} relating the light response to the membrane motion:

$$\chi_{\alpha}(\omega) = \frac{\bar{\alpha}}{(\Delta - \omega + i\frac{\kappa}{2})/\omega' - \bar{x}}. \quad (10)$$

(8) leads to

$$-\omega^2\delta x_{\pm} = -\omega_M^2\delta x_{\pm} \mp i\omega\Gamma_M\delta x_{\pm} + \mathcal{P}(\bar{\alpha}^*\delta\alpha_{\pm} + \bar{\alpha}\delta\alpha_{\mp}^*) + f_{\pm} \quad (11)$$

After inserting $\delta\alpha_{\pm}$ and using $\delta x_{\pm} = \delta x_{\mp}^*$, we find the mechanical response

$$\delta x_{\pm} = \chi(\pm\omega)f_{\pm}, \quad (12)$$

where the mechanical susceptibility of the membrane has been modified due to the optomechanical coupling:

$$\chi^{-1}(\omega) = \omega_M^2 - \omega^2 + i\omega\Gamma_M + \Sigma(\omega). \quad (13)$$

All the novel effects are contained in the optomechanical “self-energy”

$$\Sigma(\omega) = -\mathcal{P}(\bar{\alpha}^*\chi_{\alpha}(\omega) + \bar{\alpha}\chi_{\alpha}^*(-\omega)). \quad (14)$$

The optomechanical damping rate may now be read off from the imaginary part of the susceptibility, evaluated at the membrane’s resonance frequency:

$$\Gamma_{\text{opt}} = \text{Im}[\Sigma(\omega_M)]/\omega_M, \quad (15)$$

which yields the known result for optical damping:

$$\Gamma_{\text{opt}} = \omega' \frac{\mathcal{P}}{2\omega_M} |\bar{\alpha}|^2 \frac{\kappa}{2} \left\{ \frac{1}{[\omega_M - \Delta + \bar{x}\omega']^2 + \left(\frac{\kappa}{2}\right)^2} - \frac{1}{[-\omega_M - \Delta + \bar{x}\omega']^2 + \left(\frac{\kappa}{2}\right)^2} \right\} \quad (16)$$

which is the difference between the rate of Stokes and anti-Stokes transitions.

The prefactor is equal to $-x_{\text{ZPF}}^2\omega_R^2\bar{n}\kappa/L^2$, where $x_{\text{ZPF}}^2 = \hbar/(2m\omega_M)$. Therefore, the optical damping rate is seen to obey the simple formula (see [31])

$$\Gamma_{\text{opt}} = \frac{x_{\text{ZPF}}^2}{\hbar^2} [S_{FF}(\omega_M) - S_{FF}(-\omega_M)], \quad (17)$$

where S_{FF} is the spectrum of radiation pressure force fluctuations.

The damping rate is positive at negative detuning ($\Delta - \omega'\bar{x} < 0$), corresponding to cooling, while it is negative at positive detuning, leading to an increase in the mechanical quality factor, parametric amplification, and, potentially, the onset of self-induced oscillations (once $\Gamma_{\text{opt}} + \Gamma_M < 0$) [34].

Likewise, the shift of the mechanical resonance frequency (optical spring effect) is obtained from the real part:

$$\delta\omega_M = \text{Re}[\Sigma(\omega_M)]/(2\omega_M). \quad (18)$$

4.2. Linearized dynamics of dispersively-coupled optomechanical systems

We now turn to the “dispersive” optomechanical device. We model it by considering only two modes, residing to the left and to the right of the membrane. This is the correct description in the limit of a completely reflecting membrane. We consider the first deviation from that limit, i.e. the mode amplitudes α_L and α_R are coupled by photon tunneling through the membrane, at a frequency g (the tunneling amplitude). When the membrane moves to the right, the frequency of the right mode increases, while that of the left mode decreases. They are degenerate at $x = 0$, but the tunneling introduces a splitting and leads to new eigenmodes that are symmetric and antisymmetric combinations, as expected for any level anticrossing.

These features are incorporated into the following equations of motion:

$$\dot{\vec{\alpha}} = \mathcal{M}\vec{\alpha} + \begin{bmatrix} \frac{\kappa_L}{2} \\ 0 \end{bmatrix}, \quad (19)$$

where

$$\vec{\alpha} = \begin{bmatrix} \alpha_L \\ \alpha_R \end{bmatrix}; \quad \mathcal{M} = \begin{bmatrix} i(\Delta - \omega'x) - \frac{\kappa_L}{2} & -ig \\ -ig & i(\Delta + \omega'x) - \frac{\kappa_R}{2} \end{bmatrix} \quad (20)$$

Again, $\alpha_{L/R}$ have been rescaled such that in the absence of coupling they would reach a value of 1 at resonance for illumination of the left/right cavity (though in the situation assumed here, the illumination is only from the left side, as displayed by the inhomogeneous term in 19)). Δ is the detuning of the laser from the (uncoupled) resonance at $x = 0$. We have assumed a real-valued tunnel coupling amplitude g . Note that the phase of an arbitrary complex amplitude g could be eliminated by incorporating these phases into the definition of α_L and α_R . The optical resonances in the presence of coupling can be found by setting $\det\mathcal{M}(\Delta) = 0$ (with $\kappa_L = \kappa_R = 0$):

$$\omega_{\text{cav},\pm}(x) = \pm\sqrt{g^2 + (\omega'x)^2} \quad (21)$$

Comparing this with the general expression for the dispersion, $\omega_{\text{cav}}(x) = (c/L)\cos^{-1}(r_d\cos(4\pi x/\lambda))$, near the degeneracy point and for $r_d \rightarrow 1$, we find the following relations to the dispersive device’s parameters:

$$g = (c/L)\sqrt{2(1-r_d)} \quad \text{and} \quad \omega' = -\omega_L/(L/2), \quad (22)$$

where it should be noted that L is the full cavity length (comprising both halves), and $\sqrt{2(1-r_d)} \approx |t_d|$ is the transmission amplitude of the membrane. Note that in expressions of this kind (like the one for ω'), the optical frequency ω_L is assumed to be that of the original modes at the degeneracy point (small deviations do not matter here). The membrane’s equation of motion is of the form

$$\ddot{x} = -\omega_M^2(x - x_0) - \Gamma_M\dot{x} + \mathcal{P}(|\alpha_L|^2 - |\alpha_R|^2) \quad (23)$$

For simplicity, we have assumed the two halves of the cavity to be of the same length, which is the situation realized in the experiment (otherwise one would need to distinguish between ω'_L and ω'_R as well as $\mathcal{P}_L$ and $\mathcal{P}_R$).

Once again, first the steady state solution is found from the system of equations

$$\bar{\alpha} = -\frac{\kappa_L}{2}\mathcal{M}^{-1}\begin{bmatrix} 1 \\ 0 \end{bmatrix} \quad (24)$$

$$0 = -\omega_M^2(\bar{x} - x_0) - \Gamma_M\dot{x} + \mathcal{P}(|\bar{\alpha}_L|^2 - |\bar{\alpha}_R|^2). \quad (25)$$

Linearization around this solution and splitting into positive and negative frequency components as before leads to

$$\pm i\omega\delta\bar{\alpha}_{\pm} = -i\omega'\sigma_z\bar{\alpha}\delta x_{\pm} + \bar{\mathcal{M}}\delta\alpha_{\pm}, \quad (26)$$

where $\bar{\mathcal{M}}$ contains $\bar{x}$ and σ_z is the Pauli matrix. Thus, we find $\delta\bar{\alpha}_{\pm} = \vec{\chi}_{\alpha}(\pm\omega)\delta x_{\pm}$, with

$$\vec{\chi}_{\alpha}(\omega) = -\omega'[i\omega - \bar{\mathcal{M}}]^{-1}i\sigma_z\bar{\alpha}. \quad (27)$$

The mechanical susceptibility, obtained by solving the linearized equation for δx , is analogous to that found for the standard setup, see (13), except for containing radiation pressure terms from both the left and the right half-cavity:

$$\begin{aligned} \Sigma(\omega) = & -\mathcal{P}(\bar{\alpha}_L^*\chi_{\alpha}^L(\omega) + \bar{\alpha}_L\chi_{\alpha}^{L*}(-\omega)) \\ & + \mathcal{P}(\bar{\alpha}_R^*\chi_{\alpha}^R(\omega) + \bar{\alpha}_R\chi_{\alpha}^{R*}(-\omega)), \end{aligned} \quad (28)$$

where $\chi_{\alpha}^{L/R}$ refer to the two components of the vector $\vec{\chi}_{\alpha}$. The optomechanical damping rate (and the spring effect) can now be obtained as before, from (15) and (18), by inserting (28). There is little point in displaying these lengthy expressions explicitly, so we will instead discuss the results in terms of plots, for the case of $\kappa_L = \kappa_R = \kappa$.

4.3. Discussion

The diagram of damping rate Γ_{opt} vs. membrane position $\bar{x}$ and detuning Δ (both measured in units of the optical resonance width) is shown in figure 10. Γ_{opt} is determined by only two dimensionless parameters. These are the ratio of the membrane frequency ω_M to the cavity ringdown rate κ and the ratio of the photon “tunneling” rate g to κ :

$$\frac{\omega_M}{\kappa} \text{ and } \frac{g}{\kappa}$$

As long as the two optical resonances (i.e. the upper and the lower parts of the hyperbolic detuning curve) are separated by more than $\max(\omega_M, \kappa)$, they can essentially be treated individually. In that case, the behaviour of the damping rate Γ_{opt} in the vicinity of each resonance is qualitatively the same as for a standard “reflective” setup. That means Γ_{opt} is positive (negative) for laser light red-detuned (blue-detuned) with respect to the




Figure 10. (a) The cooling rate Γ_{opt} for the membrane-in-the-middle setup, as a function of laser frequency detuning (with respect to the degeneracy point) and membrane displacement. Blue (red) corresponds to cooling (amplification). Parameters are $g/\kappa = 2$ and $\omega_M/\kappa = 1$. (b) Cross-sections of the preceding plot, taken for several membrane positions: $\bar{x} \cdot |\omega'|/\kappa = 0, 0.5, 1, 1.5, 2, 4, 8$. (c) Maximizing the cooling rate, as a function of membrane position, for various coupling strengths g . Note that the position has been rescaled by g , and the curves coincide for large $g \gg \omega_M, \kappa$. They saturate towards large displacements $\bar{x}$, to the value given by the simple theory for the standard setup, while Γ_{opt} vanishes at $\bar{x} = 0$ (see text) for large g . For small g , the maximum cooling rate can even become larger than the standard limit (see curve labeled $g/\kappa = 0.5$). Note that Γ_{opt} was maximized over the half-plane $\Delta \leq 0$, where the global maximum of Γ_{opt} is located when $\bar{x} > 0$ (the plot would be inverted with respect to $\bar{x} < 0$ if we were to maximize over $\Delta \geq 0$).

resonance, i.e. one has cooling (or amplification) for $\omega_L < \omega_{\text{res}}$ ($\omega_L > \omega_{\text{res}}$). When ω_M/κ is small, the maximum $|\Gamma_{\text{opt}}|$ is reached for a detuning of $\pm\kappa/2$ (the point of maximum slope in the intensity-vs-detuning curve). In the resolved-sideband regime $\omega_M \gg \kappa$, the maximum is reached at $\pm\omega_M$. The only quantitative difference is brought about by the change in the slope $\partial\omega_{\text{res}}/\partial x$, which is directly proportional to the net radiation pressure force acting on the membrane. As the slope goes to zero near the avoided crossing, so does $\Gamma_{\text{opt}} \propto (\partial\omega_{\text{res}}/\partial x)^2$. Note that this is a result of our weak coupling approximation and linearization of the equations of motion. Inclusion of higher order terms would permit two-phonon Raman processes which can lead to cooling for red detunings of $2\omega_M$. In addition, the circulating power is smaller when most of the light is stored in the right half of the cavity (since we assume illumination from the left), and therefore the cooling rate is correspondingly reduced on that branch (with positive slope $\partial\omega_{\text{res}}/\partial x$), as can be seen in figure 11. On the amplification side ($\Gamma_{\text{opt}} < 0$), the membrane may settle into a state of self-sustained oscillations when $\Gamma_{\text{opt}} + \Gamma_M$ becomes negative. Those regions of instability can therefore directly be read off diagrams such as those in figure 11, once the mechanical damping rate Γ_M is given.

When the resonances touch, i.e. when they get closer than $\max(\omega_M, \kappa)$, the regions of cooling and amplification become visibly distorted, with intricate patterns as a result. In any case however, the diagrams remain inversion symmetric around the degeneracy point (upon simultaneous change of the sign of Γ_{opt}).

The physics of this regime can best be understood by analyzing the cases where the mechanical frequency ω_M becomes comparable to or even larger than the splitting $2g$ of the dispersion relation, while the ring-down rate remains small. For the following discussion, we therefore refer the reader to the lower right panel of figure 11 ($g/\kappa = 1$ and $\omega_M/\kappa = 4$). As seen in that figure, the cooling or heating rate is apparently maximal at places where the incoming radiation is in resonance either with the optical eigenfrequencies $\omega_{\text{cav},\pm}(x)$, or with their sidebands $\omega_{\text{cav},\pm}(x) \pm \omega_M$ (full and dashed lines in that panel). The rate becomes particularly pronounced when these dispersion curves cross. At these places, there is interference between the eigenmode that is nearby in frequency, and the excitation of the other eigenmode via Raman scattering. Indeed, this interference is necessary to explain the remarkable fact that there can be some cooling or heating even at $x = 0$, particularly when $2g$ becomes smaller than ω_M : At the degeneracy point $x = 0$, we have the eigenmodes as symmetric and antisymmetric combinations of the basis modes, $\alpha_{\pm} = (\alpha_L \pm \alpha_R)/\sqrt{2}$. Consequently, the radiation pressure force

$$F_{\text{rad}} \propto |\alpha_L|^2 - |\alpha_R|^2 \propto |\alpha_+ + \alpha_-|^2 - |\alpha_+ - \alpha_-|^2 \quad (29)$$

vanishes identically, unless there is interference between α_+ and α_- . This can happen at the points where the dispersions $\omega_{\pm,\text{cav}}(x)$ and $\omega_{\pm,\text{cav}}(x) \pm \omega_M$ cross. It also happens elsewhere, to a lesser extent, due to the finite cavity ring-down rates $\kappa_{L,R}$, which broaden the resonances. The strongest effect is observed when $\omega_M = 2g$, where the resonance conditions are fulfilled simultaneously right at the degeneracy point (see Fig. 11, panel with $g/\kappa = 2$, $\omega_M/\kappa = 4$; and Fig. 10(c), $g/\kappa = 0.5$, $\omega_M/\kappa = 1$). On the other hand, the effect vanishes in the limit $\omega_M/g \rightarrow 0$. In that limit, the standard picture is sufficient, when taking into account the suppression of the slope $\partial\omega_{\text{cav}}(x)/\partial x$ at the degeneracy point, which reduces the cooling and heating rates to zero.

In summary, in a certain regime it is possible to cool the membrane even at $x = 0$ (i.e., where the bands are flat). This discussion may be important for experiments in which the membrane is kept at $x = 0$ to realize a phonon QND measurement, as described in Ref. [19].

5. Signatures of quantum behaviour in a weak energy measurement

As has been discussed above and elsewhere [19], a dispersive optomechanical device can be operated in a regime where the cavity frequency depends directly on x^2 , the position-squared of a macroscopic mechanical oscillator. As a result, one can make a direct measurement of the oscillator's energy $E = \hbar\omega_M(n + 1/2)$ where n is the number of phonons in the membrane [19]. One drives the cavity on resonance and measures the phase of the transmitted beam; this phase is proportional to E . We thus have the possibility to detect a truly quantum aspect of the oscillator: the quantization of its energy. Note that this is impossible to do with a linear position detector (e.g. a cavity whose frequency depends directly on x), as in this case one measures both




Figure 11. The optomechanical cooling rate in the MIM setup near a degeneracy point. These plots show Γ_{opt} as a function of membrane position $|\omega'|\bar{x}/\kappa$ (horiz.) and detuning Δ/κ (vert.), for various values of ω_M/κ and g/κ . Blue refers to cooling ($\Gamma_{\text{opt}} > 0$), red to heating or amplification ($\Gamma_{\text{opt}} < 0$).

the energy *and* phase of the oscillator, and is thus subject to the usual limitations imposed by quantum back-action [35]. All recent experiments in optomechanics and electromechanical systems have (to the best of our knowledge) employed linear position detectors, and are hence subject to these limitations.

While having a non-linear coupling to the oscillator is certainly a prerequisite to detecting the quantum nature of its energy, it is not in itself enough: one also needs to consider the output noise of the detector. Here, this output noise consists of the

shot noise in the transmitted beam through the cavity, plus any additional technical noise associated with determining the phase of this beam. If this measurement was truly QND, this output noise would not be a problem: one could achieve any desired sensitivity by simply averaging the output signal for a sufficiently long time [35]. The back-action of a perfect QND measurement does not affect the measured observable, and thus the oscillator's energy would not fluctuate during the measurement. However, this is not the case for any real experiment, which is performed at some small but non-zero temperature. Because of this small temperature and the non-zero oscillator damping, the oscillator's energy will indeed fluctuate if one waits long enough. There is thus a limit to how long one can average, and thus to how well one can resolve the quantum nature of the oscillator's energy.

In this section, we will address quantitatively the limitations on detecting quantum behaviour arising from the combination of the weak nature of the measurement and the unavoidable (thermal) fluctuations in the oscillator energy. We will focus on the realistic case where one can only obtain an energy resolution corresponding to a single quanta after averaging for a time comparable to (or longer than) the lifetime of a phonon Fock state. As such, one is no longer truly measuring the instantaneous energy of the oscillator; instead, one is measuring the time-integrated energy fluctuations of the oscillator. We will calculate this quantity for both a classical and a quantum dissipative oscillator, and will discuss whether differences between the two are experimentally resolvable. We will focus throughout on the experimental conditions proposed in Ref. [19]. In particular, we assume a situation where the oscillator is initially near its ground state, but is coupled to a dissipative bath with a temperature $T_{\text{bath}} \gg \hbar\omega_M/k_B$. In the proposed experiment this is realized by laser-cooling the membrane to its ground state and then shutting off the cooling beam while an energy measurement is made. Note that the somewhat related situation of QND measurement of qubit energy was studied theoretically in Ref. [36].

5.1. Model and measurement sensitivity in the zero-damping limit

The quantity measured in the experiment is the phase shift of the transmitted beam through the cavity (or, equivalently, the error signal in a Pound-Drever-Hall setup); by dividing out a proportionality factor (the “gain” of the measurement), one can refer this signal back to the mechanical oscillator, expressing it as a number of quanta $\tilde{n}(t)$:

$$\tilde{n}(t) = n(t) + \xi(t) \quad (30)$$

where $n(t)$ is the actual number of oscillator quanta, and $\xi(t)$ is the added noise of the measurement. We take $\xi(t)$ to be Gaussian white noise with a (two-sided) spectral density S_{nn} , i.e.:

$$\langle \xi(t_1)\xi(t_2) \rangle = S_{nn}\delta(t_1 - t_2) \quad (31)$$

For the cavity system and a shot-noise limited Pound-Drever-Hall measurement, one has:

$$S_{nn} = \frac{\hbar c \lambda^3 (1 - r_c)}{4096 \pi F^2 P_{\text{in}} x_m^4} \quad (32)$$

Note that S_{nn} depends both on the amount of output noise in the measurement, and on the strength of the cavity - oscillator coupling.

We will be interested throughout in the case of a weak measurement, where one must time-average the output signal to counteract the effects of the added noise. We are thus led to the quantity $\tilde{m}(t)$, the time-integral of the inferred number of quanta $\tilde{n}(t)$:

$$\begin{aligned} \tilde{m}(t_{\text{avg}}) &= \int_0^{t_{\text{avg}}} dt' \tilde{n}(t') = \int_0^{t_{\text{avg}}} dt' n(t') + \int_0^{t_{\text{avg}}} \xi(t') \\ &\equiv m(t_{\text{avg}}) + \int_0^{t_{\text{avg}}} \xi(t') \end{aligned} \quad (33)$$

As the added noise is white, the probability distribution $P_{\text{meas}}(\tilde{m}, t_{\text{avg}})$ for the measured quantity $\tilde{m}$ is a simple convolution of a Gaussian and the probability distribution $P(m)$ of the true oscillator energy fluctuations m :

$$P_{\text{meas}}(\tilde{m}, t_{\text{avg}}) = \int dm' \left[P(\tilde{m} - m', t_{\text{avg}}) \cdot \frac{1}{\sqrt{2\pi (\sigma_n t_{\text{avg}})^2}} \exp\left(-\frac{(m'/t_{\text{avg}})^2}{2\sigma_n^2}\right) \right] \quad (34)$$

with

$$\sigma_n(t_{\text{avg}}) = \sqrt{\frac{S_{nn}}{t_{\text{avg}}}} \quad (35)$$

Consider first the ideal case where the measurement is completely back-action free, and where the oscillator damping $\gamma \rightarrow 0$, meaning that there are no thermal energy fluctuations. In this case, if the oscillator starts with n_0 quanta, it will always have n_0 quanta: $P(m, t_{\text{avg}}) = \delta(m - n_0 t_{\text{avg}})$. The distribution of $\tilde{m}$ is then just a Gaussian:

$$P_{\text{meas}}(\tilde{m}, t_{\text{avg}}) = \frac{1}{\sqrt{2\pi (\sigma_n t_{\text{avg}})^2}} \exp\left(-\frac{(\tilde{m}/t_{\text{avg}} - n_0)^2}{2\sigma_n^2}\right) \quad (36)$$

To see evidence of the oscillator's quantum nature, we would like to be able to resolve Fock states that differ by a single quanta. For $\gamma = 0$, these two states will each give Gaussian distributions of $\tilde{m}$ having means separated by t_{avg} . As is standard, we can describe the distinguishability of these two Gaussians by a signal to noise ratio $R_{SNR}(t_{\text{avg}})$. This is simply the ratio of the signal power to the noise power:

$$R_{SNR}(t_{\text{avg}}) = \frac{[\langle \tilde{m} \rangle_1 - \langle \tilde{m} \rangle_2]^2}{(\Delta \tilde{m}_1 + \Delta \tilde{m}_2)^2} = \frac{t_{\text{avg}}^2}{(2t_{\text{avg}}\sigma_n)^2} = \frac{t_{\text{avg}}}{4S_{nn}} \quad (37)$$

where $\Delta \tilde{m}_1$ denotes the standard deviation of $\tilde{m}$ for the first Gaussian distribution, etc. As expected, $R_{SNR}(t_{\text{avg}})$ can be made arbitrarily large by increasing the averaging time t_{avg} . In particular, the two Gaussians become resolvable (i.e. the averaged distribution has two as opposed to one maximum) when $R_{SNR}(t_{\text{avg}}) \geq 1^\ddagger$.

[‡] Note that our definition of the SNR ratio is smaller by a factor of two than the SNR ratio Σ used in Ref. [19]

5.2. Distinguishing quantum from classical when $\gamma > 0$

The story becomes somewhat more complicated when we now include the unavoidable fluctuations of $n(t)$. We will consider the experimentally relevant case where these fluctuations are *only* due to the dissipative bath coupled to the oscillator, and not to the back-action of the measurement. As discussed in Ref. [19], there is a small back-action effect associated with the fact that the cavity is coupled to x^2 and not the oscillator energy; this however is a much weaker effect than the thermal fluctuations we consider. The thermal bath coupled to the oscillator will cause a given oscillator Fock state $|n\rangle$ to decay at a rate Γ_n . A simple golden rule calculation yields:

$$\Gamma_n = \gamma [n_{\text{eq}} + n(2n_{\text{eq}} + 1)] \quad (38)$$

where γ is the damping rate of the oscillator,

$$n_{\text{eq}} = \left(\exp \left[\frac{\hbar \omega_M}{k_B T_{\text{bath}}} \right] - 1 \right)^{-1}, \quad (39)$$

and T_{bath} is the bath temperature.

Due to these thermal fluctuations, the distribution of the measured quantity $\tilde{m}$ will not be Gaussian. To obtain a very rough estimate of whether our measurement can still resolve quantum energy behaviour, we could still attempt to use the SNR ratio derived above; this was the approach taken in [19]. We assume that we start in the ground state (to maximize the Fock state lifetime $1/\Gamma_n$), and use an averaging time equal to the lifetime of this state. Letting $\tau = 1/\Gamma_0$ represent the lifetime of the ground state, we thus have as an approximate figure of merit :

$$R \equiv R_{\text{SNR}}(t_{\text{avg}} = \tau) = \frac{\tau}{4S_{nn}} = \frac{1}{4\gamma n_{\text{eq}} S_{nn}} \quad (40)$$

One might guess that if $R > 1$, one can resolve quantum aspects of the oscillator's energy; in [19], it was shown that achieving $R \sim 1$ could be possible in the next generation of experiments. However, the condition $R > 1$ is clearly an approximate one, as it neglects all the complexities arising from the fluctuations of the oscillator. In particular, the two distributions one is trying to distinguish are not Gaussian, and thus it is by no means clear that the SNR ratio R will remain a good measure of distinguishability.

We will now assess more accurately the conditions required to resolve quantum-classical differences. The first step will be to ignore the added noise of the detector, and focus on the probability distribution of the “true” time-integrated oscillator energy m . We will do this in both the cases of a classical oscillator and a quantum oscillator; the respective distributions will be denoted $P_{\text{cl}}(m, t_{\text{avg}})$ and $P_{\text{q}}(m, t_{\text{avg}})$. Having these distributions, we will then add the effects of the added noise S_{nn} , and ask whether the corresponding *measured* distributions $P_{\text{meas,cl}}(m, t_{\text{avg}})$ and $P_{\text{meas,q}}(m, t_{\text{avg}})$ (as given by (34)) are distinguishable for a given level of noise and averaging time. As the distributions involved will be non-Gaussian, we will need to use a more sophisticated measure of distinguishability than the signal-to-noise ratio R used in the Gaussian case. We will make use of an information-theoretic measure, the accessible information $\mathcal{I}$.

We start with the first step of our program: what are the probability distributions of the true integrated oscillator energy fluctuations m ? Given the relative weakness of cavity-oscillator couplings, we will necessarily need to use averaging times comparable to or even longer than the lifetimes of oscillator Fock states. As a result, the experiment is no longer about measuring the instantaneous energy of the oscillator. Rather, we are asking whether one can see quantum behaviour in the energy fluctuations of the oscillator. The quantities we wish to calculate ($P_q(m, t_{\text{avg}})$ and $P_{\text{cl}}(m, t_{\text{avg}})$) are thus formally analogous to the well-studied full counting statistics of charge in mesoscopic electron systems [37]; there, one wishes to calculate the statistics of the time-integrated current through a mesoscopic conductor. Given this similarity, we can employ a similar calculational technique in our problem. This was essentially done in Ref. [38], where the motivation was to describe an experiment where a qubit is used to detect Fock states in a nanoresonator. One calculates the dephasing of a qubit whose energy is directly proportional to the energy of a dissipative oscillator; this immediately yields the generating function of $P_q(m, t_{\text{avg}})$, $\tilde{P}_q(\lambda, t_{\text{avg}})$, defined by:

$$\tilde{P}_q(\lambda, t_{\text{avg}}) = \int_{-\infty}^{\infty} dm e^{-i\lambda m} P_q(m, t_{\text{avg}}) \quad (41)$$

In Ref. [38], the focus was to understand the time-dependence of $\tilde{P}_q(\lambda, t_{\text{avg}})$, and hence the dephasing spectrum of the qubit. Here, the focus will instead be on its λ dependence, as the Fourier transform of $\tilde{P}_q(\lambda, t_{\text{avg}})$ will yield the desired distribution $P_q(m, t_{\text{avg}})$.

Consider the initial condition corresponding to the proposed experiment: the oscillator is initially in a thermal state corresponding to a temperature T_{init} which differs from the bath temperature T_{bath} . Using the method of Ref. [38], one finds that the corresponding generating function for a quantum oscillator is given by:

$$\tilde{P}_q(\lambda, t) = e^{\gamma t/2} e^{-i(\alpha - \lambda)t/2} \frac{1 - M}{1 - M e^{-i\alpha t}} \quad (42)$$

with

$$\alpha = \sqrt{(\lambda - i\gamma)^2 - 4i\lambda\gamma n_{\text{eq}}} \quad (43a)$$

$$M = \frac{2\lambda n_{\text{init}} - (\alpha - \lambda + i\gamma)}{2\lambda n_{\text{init}} + (\alpha + \lambda - i\gamma)} \quad (43b)$$

Here, n_{eq} is the Bose-Einstein factor associated with the bath temperature (cf. (39)), while n_{init} is the Bose-Einstein factor associated with the initial oscillator temperature T_{init} .

For comparison purposes, we also require $P_{\text{cl}}(m, t_{\text{avg}})$, the distribution of m for a classical dissipative oscillator. To obtain this, we use $\tilde{P}_q(\lambda, t_{\text{avg}})$ in (42) to find $P_{E,q}(s, t_{\text{avg}})$ the distribution of integrated oscillator *energy* fluctuations $s = \hbar\omega(m + t_{\text{avg}}/2)$; this involves a simple change of variables. It is then straightforward to take the classical $\hbar \rightarrow 0$ limit to find $P_{E,\text{cl}}(s, t_{\text{avg}})$. Defining the corresponding generating function via:

$$\tilde{P}_{E,\text{cl}}(\chi, t_{\text{avg}}) = \int ds e^{-i\chi s} P_{E,\text{cl}}(s, t_{\text{avg}}) \quad (44)$$

we find:

$$\tilde{P}_{E,\text{cl}}(\chi, t) = e^{\gamma t/2} e^{-i\alpha_{\text{cl}} t/2} \frac{1 - M_{\text{cl}}}{1 - M_{\text{cl}} e^{-i\alpha t}} \quad (45)$$

with

$$\alpha_{\text{cl}} = \sqrt{-\gamma^2 - 4ik_B T_{\text{bath}} \chi \gamma} \quad (46)$$

$$M_{\text{cl}} = \frac{2k_B T_{\text{init}} \chi - (\alpha_{\text{cl}} + i\gamma)}{2k_B T_{\text{init}} \chi + (\alpha_{\text{cl}} - i\gamma)} \quad (47)$$

The corresponding classical distribution of m , $P_{\text{cl}}(m, t)$, follows from:

$$\tilde{P}_{\text{cl}}(\lambda, t) = P_{E,\text{cl}}\left(\chi = \frac{\lambda}{\hbar\omega_M}, t\right) e^{i\lambda t/2} \quad (48)$$

While the form of the classical generating function $\tilde{P}_{E,\text{cl}}(\chi, t)$ may seem unfamiliar, it is easy to check its behaviour in some simple limits. For example, consider the limit where $\gamma \rightarrow 0$. Equation (44) then yields:

$$\tilde{P}_{E,\text{cl}}(\chi) \rightarrow \frac{1}{i\chi k_B T_{\text{init}} + 1} \quad (49)$$

which corresponds to a simple Boltzman distribution as expected:

$$P_{E,\text{cl}}(s, t) = \frac{1}{k_B T_{\text{init}} t} \exp\left(-\frac{(s/t)}{k_B T_{\text{init}}}\right) \quad (50)$$

We now have analytic expressions for the distribution of time-integrated energy fluctuations of both a classical oscillator ($P_{\text{cl}}(m, t)$, cf. (48)) and a quantum oscillator ($P_{\text{q}}(m, t)$, cf. (42)). The corresponding distributions of the measured quantity $\tilde{m}$ can be easily found by including the effects of the added noise S_{nn} via (34); we denote these (respectively) as $P_{\text{meas},\text{cl}}(m)$ and $P_{\text{meas},\text{q}}(m)$. To assess how different these two (non-Gaussian) distributions are from one another, we will consider their mutual information $\mathcal{I}$. This measure of distinguishability is defined as [39]:

$$\mathcal{I}[P_1, P_2] = H[(P_1 + P_2)/2] - \frac{1}{2} (H[P_1] + H[P_2]) \quad (51)$$

where $H[P]$ is the Shannon entropy of the distribution P :

$$H[P] := \int dm P(m) \log_2 P(m) \quad (52)$$

We can interpret the first term in Eq. (50) as the information in a signal in which each instance is drawn randomly from either P_1 or P_2 . The second term is the average information under the same circumstances except that we are told from which distribution the signal is drawn. If telling us which distribution was used makes no difference then the two distributions are identical and the mutual information is zero. The larger the value of the mutual information $\mathcal{I}[P_1, P_2]$, the more distinguishable are the two distributions P_1 and P_2 . $\mathcal{I}$ is a convenient measure both because it is applicable to arbitrary distributions P_1 and P_2 , and because it has a direct information-theoretic interpretation in terms of information transmission rates down noisy communication channels [39]. We note for two Gaussian distributions with identical standard deviations, $\mathcal{I} \simeq 0.49$ when $R_{\text{SNR}} = 1$, while $\mathcal{I} \rightarrow 1$ for $R_{\text{SNR}} \gg 1$.




Figure 12. Quantum jump traces in the presence of noise and temporal averaging, for different noise strengths ((a) and (b)) and increasing averaging time (top to bottom). The plots show the traces $\langle \tilde{n}(t) \rangle_t$ that would be observed by doing a sliding time-average of $n(t)$, including the noise $\xi(t)$. Here the time-average was done by convoluting with a Gaussian whose width is set by $\tilde{t}_{\text{avg}}$, in such a way as to have the simple relation $\langle \langle \xi \rangle_t^2 \rangle = S_{nn}/\tilde{t}_{\text{avg}}$. The noise strength has been chosen as $S_{nn}/\tau = 0.001$ and $S_{nn}/\tau = 0.004$ in (a) and (b), respectively. The time-interval displayed in each curve is 2τ , where τ is the ground state lifetime. From top to bottom, successive curves arise from the same trace by averaging over increasing time-intervals: $\tilde{t}_{\text{avg}}/\tau = 0.01, 0.05, 0.1, 0.2, 0.5, 1.0$. Curves have been displaced horizontally and vertically for clarity. The values of a signal-to-noise ratio, defined in correspondence to the discussion in the main text, are (from top to bottom): (a) $\tilde{t}_{\text{avg}}/(4S_{nn}) = 2.5, 12.5, 25, 50, 125, 250$ and (b) $0.625, 3.125, 6.25, 12.5, 31.25, 62.5$.

5.3. Results

Equations (34), (42) and (48) can now be used to quantitatively assess whether quantum versus classical differences can be resolved under a variety of different experimental conditions. In what follows, we will present only a few selected results relevant to the experiment proposed in Ref. [19].

5.3.1. Measurement runs starting in the oscillator ground state We first consider the ideal situation where the oscillator has been cooled to its ground state: $T_{\text{init}} = n_{\text{init}} = 0$. The cooling beam is then shut off, and the number-state measurement is made. During this time, the oscillator rapidly heats up due to its coupling to the equilibrium heat bath at temperature T_{bath} . We will focus on the experimentally relevant case where $\gamma \ll \omega_M$, $n_{\text{eq}} \gg 1$, and on averaging times small enough that the average number of quanta in




Figure 13. Left: distinguishability of quantum versus classical energy fluctuations, as measured by the mutual information $\mathcal{I}[P_{\text{meas,q}}, P_{\text{meas,cl}}]$, versus the inverse added noise $R = 1/(4S_{nn}\tau)$. In each case, we have used an optimal averaging time t_{avg} which maximizes $\mathcal{I}$ and have started the oscillator in the ground state $n_{\text{init}} = 0$. Following Ref. [19], we have taken $\omega_M/2\pi = 10^5\text{Hz}$, $\gamma/\omega_M = 1.2 \times 10^{-7}$ and $T_{\text{bath}} = 300\text{mK}$. Finally, we have shifted the quantum distribution so that both the quantum and classical distributions have the same mean, as in experiment, this shift of the mean would be hard to detect. Note that an SNR ratio of $R = 1$ in the Gaussian case corresponds to $\mathcal{I} \simeq 0.49$. Right: optimal averaging time versus R , same parameters.

the oscillator remains much smaller than n_{eq} . In this regime, the oscillator damping γ and the bath temperature T_{bath} essentially only enter via the time-scale τ , the lifetime of the $n = 0$ Fock state. It is this time-scale which determines the initial heating-up of the oscillator:

$$\langle \hat{n}(t) \rangle = n_{\text{eq}}(1 - e^{-\gamma t}) \quad (53)$$

$$\simeq \gamma n_{\text{eq}} t = t/\tau \quad (54)$$

Given these conditions, there are two relevant questions. First, given a certain noise level S_{nn} , what is the optimal averaging time? Second, given that we have optimized the averaging time, how does the distinguishability depend on S_{nn} ?

To illustrate this process, we show a series of calculated time traces corresponding to such a scenario in figure 12 for various values of the averaging time. In the left panel of figure 13, we show how the measurable distinguishability between the classical and quantum distributions depends on the noise level S_{nn} , as parameterized by R (cf.(40)). The distinguishability is measured by the mutual information $\mathcal{I}$ between the expected experimental distributions for a classical and quantum oscillator ($P_{\text{meas,cl}}(m)$ and $P_{\text{meas,q}}(m)$ respectively). Each run corresponds to starting the oscillator in the ground state and using an averaging time which maximizes $\mathcal{I}$; the value of the averaging time is shown in the right panel of figure 13. Note that before computing the mutual information $\mathcal{I}$, we have shifted the quantum distribution to remove the zero-point energy contribution (as resolving this difference in an experiment would be very difficult); the result is that both the classical and quantum distributions have identical means. We see that in general, one needs a noise level small enough that $R \gg 1$ to unambiguously




Figure 14. Distributions of the integrated output of the experiment, for both the cases of a classical oscillator ($P_{\text{meas,cl}}(m)$, dashed blue) and a quantum oscillator ($P_{\text{meas,q}}(m)$, solid red) oscillator. Following Ref. [19], we have taken $\omega_M/2\pi = 10^5\text{Hz}$, $\gamma/\omega_M = 1.2 \times 10^{-7}$ and $T_{\text{bath}} = 300\text{mK}$. In each case, the oscillator starts in the ground state, and an optimal averaging time has been used; we have also shifted the quantum distribution in each case to remove the zero-point shift in the average. The four panels correspond to different levels of added noise S_{nn} : $R = 200$ (top left), $R = 61$ (top right), $R = 11$ (bottom left) and $R = 1$ (bottom right). In each plot, the range of m has been chosen to display 90% of the area of the quantum curve.

resolve classical-quantum differences: the simple Gaussian estimate which suggests $R \sim 1$ is sufficient is too optimistic. Classical and quantum distributions of m for different values of R are shown in figure 14.

5.3.2. Starting at a finite temperature It is also interesting to ask what happens if the oscillator does not start in the ground state (i.e. $n_{\text{init}} > 0$). In practice, one might not be able to cool the oscillator all the way to the ground state. Even if one could cool to the ground state, it would be very useful experimentally to extract as much information as possible in one run of the experiment. We saw above that if the oscillator starts in the ground state, the optimal averaging time is on the order of τ . After this initial averaging time, the average number of quanta in the oscillator will be ~ 1 . One could imagine starting a second averaging period at this point; the question is whether the initial temperature of the oscillator will make quantum versus classical differences even




Figure 15. Left: distinguishability of quantum versus classical energy fluctuations (as measured by $\mathcal{I}[P_{\text{meas,q}}, P_{\text{meas,cl}}]$), versus initial oscillator temperature, and for a fixed noise strength corresponding to $R = 11$. Following [19], we have taken $\omega_M/2\pi = 10^5\text{Hz}$, $\gamma/\omega_M = 1.2 \times 10^{-7}$ and $T_{\text{bath}} = 300\text{mK}$. In each case we have used an optimal averaging time, and have shifted each quantum distribution so that both the quantum and classical distributions have the same mean. Right: optimal averaging time as a function of n_{initial} for the same choice of parameters.

harder to see.

In the left panel of figure 15, we consider a situation where the added noise corresponds to $R = 11$, and plot the distinguishability between $P_{\text{meas,q}}$ and $P_{\text{meas,cl}}$ (measured via $\mathcal{I}$) as a function of the initial oscillator temperature n_{init} . For each point, we have used an optimal averaging time; the dependence of this optimal time on n_{init} is shown in the right panel. As in previous plots, we have also shifted the quantum distributions so that they have the same means as the corresponding classical distributions. As could be expected, as the initial temperature increases, the distinguishability between classical and quantum distributions does indeed decrease. However, this decrease is slow enough that one could obtain useful information even if the oscillator starts at low but non-zero temperature. It is also interesting to note that while the overall distinguishability between the classical and quantum distributions decreases with initial temperature, the quantum distribution will develop multiple peaks; this is shown in figure 16.




Figure 16. Distributions of the integrated output of the experiment, for both the cases of a classical oscillator ($P_{\text{meas,cl}}(m)$, dashed blue) and a quantum oscillator ($P_{\text{meas,q}}(m)$, solid red). Following Ref. [19], we have taken $\omega_M/2\pi = 10^5\text{Hz}$, $\gamma/\omega_M = 1.2 \times 10^{-7}$ and $T_{\text{bath}} = 300\text{mK}$. In each case, we have assumed a noise level corresponding to $R = 11$, used an optimal averaging time, and have removed the zero-point shift in the average of the quantum distributions. The panels correspond to initial oscillator temperatures of $n_{\text{init}} = 0$ (top left), $n_{\text{init}} = 1$ (top right), $n_{\text{init}} = 2$ (bottom left) and $n_{\text{init}} = 4$ (bottom right). In each plot, the range of m has been chosen to display 90% of the area of the quantum curve. At higher temperatures, multiple peaks are visible, however the overall distinguishability from the classical distribution is reduced.

References

- [1] V. B. Braginski and A. B. Manukin. Ponderomotive effects of electromagnetic radiation. *Soviet Physics JETP*, 25(653), 1967.
- [2] Carlton M. Caves. Quantum-mechanical radiation-pressure fluctuations in an interferometer. *Phys. Rev. Lett.*, 45(2):75–79, Jul 1980.
- [3] S. Bose, K. Jacobs, and P. L. Knight. Scheme to probe the decoherence of a macroscopic object. *Physical Review A*, 59(3204), 1999.
- [4] W. Marshall, C. Simon, R. Penrose, and D. Bouwmeester. Towards quantum superpositions of a mirror. *Physical Review Letters*, 91(130401), September 2003.
- [5] B. S. Sheard, M. B. Gray, C. M. Mow-Lowry, D. E. McClelland, and S. E. Whitcomb. Observation and characterization of an optical spring. *Physical Review A*, 69(051801), 2004.
- [6] Constanze Hohberger Metzger and Khaled Karrai. Cavity cooling of a microlever. *Nature*, 432(7020):1002–1005, 2004.
- [7] O. Arcizet, P. F. Cohadon, T. Briant, M. Pinard, and A. Heidmann. Radiation-pressure cooling and optomechanical instability of a micro-mirror. *Nature*, 444:71, 2006.
- [8] S. Gigan H. R. Bohm M. Paternostro F. Blaser G. Langer J. B. Hertzberg K. C. Schwab D. Bauerle M. Aspelmeyer A. Zeilinger. Self-cooling of a micromirror by radiation pressure. *Nature*, 444, November 2006.
- [9] Thomas Corbitt, Yanbei Chen, Edith Innerhofer, Helge Muller-Ebhardt, David Ottaway, Henning Rehbein, Daniel Sigg, Stanley Whitcomb, Christopher Wipf, and Nergis Mavalvala. An all-optical trap for a gram-scale mirror. *Physical Review Letters*, 98(15):150802, 2007.
- [10] I. Tittonen, G. Breitenbach, T. Kalkbrenner, T. Müller, R. Conradt, S. Schiller, E. Steinsland, N. Blanc, and N. F. de Rooij. Interferometric measurements of the position of a macroscopic body: Towards observation of quantum limits. *Phys. Rev. A*, 59(2):1038–1044, Feb 1999.
- [11] C. Fabre, M. Pinard, S. Bourzeix, A. Heidmann, E. Giacobino, and S. Reynaud. Quantum-noise reduction using a cavity with a movable mirror. *Phys. Rev. A*, 49(2):1337–1343, Feb 1994.
- [12] S. Pirandola, S. Mancini, D. Vitali, and P. Tombesi. Constructing finite-dimensional codes with optical continuous variables. *EPL*, 68(3):323–329, 2004.
- [13] A. Dorsel, J. D. McCullen, P. Meystre, E. Vignes, and H. Walther. Optical bistability and mirror confinement induced by radiation pressure. *Phys. Rev. Lett.*, 51(17):1550–1553, Oct 1983.
- [14] A. Gozzini, F. Maccarrone, F. Mango, I. Longo, and S. Barbarino. Light-pressure bistability at microwave frequencies. *J. Opt. Soc. Am. B*, 2(11):1841, 1985.
- [15] Tal Carmon, Hossein Rokhsari, Lan Yang, Tobias J. Kippenberg, and Kerry J. Vahala. Temporal behavior of radiation-pressure-induced vibrations of an optical microcavity phonon mode. *Physical Review Letters*, 94(22):223902, 2005.
- [16] Young-Shin Park and Hailin Wang. Radiation pressure driven mechanical oscillation in deformed silica microspheres via free-space evanescent excitation. *Opt. Express*, 15(25):16471–16477, 2007.
- [17] A. Schliesser, R. Riviere, G. Anetsberger, O. Arcizet, and T. J. Kippenberg. Resolved sideband cooling of a micromechanical oscillator. *arXiv:0709.4036*, 2007.
- [18] C. A. Regal, J. D. Teufel, and K. W. Lehnert. Measuring nanomechanical motion with a microwave cavity interferometer. *arXiv:0801.1827v2*, 2008.
- [19] J. D. Thompson, B. M. Zwickl, A. M. Jayich, F. Marquardt, S.M. Girvin, and J.G.E. Harris. Strong dispersive coupling of a high finesse cavity to a micromechanical membrane. *Nature*, 452:72–75, March 2008.
- [20] I. Favero and K. Karrai. Cavity cooling of a nanomechanical resonator by light scattering. *arXiv*, 0707.3117v3, 2007.
- [21] P. Meystre, E. M. Wright, J. D. McCullen, and E. Vignes. Theory of radiation-pressure-driven interferometers. *Journal of The Optical Society of America B*, June 1985.
- [22] M. Bhattacharya, H. Uys, and P. Meystre. Optomechanical trapping and cooling of partially transparent mirrors. *arXiv:0708.4078v1*, 2007.

- [23] P. Meystre, M. Bhattacharya, and P. L. Giscard. Optical squeezing of a mechanical oscillator by dispersive interaction. *arXiv:0803.1219v1*, 2008.
- [24] M. Bhattacharya and P. Meystre. Multiple membrane cavity optomechanics. *arXiv:0804.1190v1*, 2008.
- [25] D. H. Santamore, A. C. Doherty, and M. C. Cross. Quantum nondemolition measurement of fock states of mesoscopic mechanical oscillators. *Physical Review B (Condensed Matter and Materials Physics)*, 70(14):144301, 2004.
- [26] Geoffrey Brooker. *Modern Classical Optics*. Oxford University Press, Oxford, New York, 2003.
- [27] R. Dandliker and T. Tschudi. Coupled resonators; critical dependence of the mutual interaction on their separation. *Appl. Opt.*, 8(6):1119, 1969.
- [28] B. M. Zwickl, W. E. Shanks, A. M. Jayich, C. Yang, A. C. Bleszynski Jayich, J. D. Thompson, and J. G. E. Harris. High quality mechanical and optical properties of commercial silicon nitride membranes. *Applied Physics Letters*, 92(10):103125, 2008.
- [29] Dana Z. Anderson. Alignment of resonant optical cavities. *Applied Optics*, 23(17):2944–2949, September 1984.
- [30] Anthony E. Siegman. *Lasers*. University Science Books, 1986.
- [31] Florian Marquardt, Joe P. Chen, A. A. Clerk, and S. M. Girvin. Quantum theory of cavity-assisted sideband cooling of mechanical motion. *Physical Review Letters*, 99(9):093902, 2007.
- [32] I. Wilson-Rae, N. Nooshi, W. Zwerger, and T. J. Kippenberg. Theory of ground state cooling of a mechanical oscillator using dynamical backaction. *Physical Review Letters*, 99(9):093901, 2007.
- [33] A. Dorsel, J. D. McCullen, P. Meystre, E. Vignes, and H. Walther. Optical bistability and mirror confinement induced by radiation pressure. *Phys. Rev. Lett.*, 51(17):1550–1553, Oct 1983.
- [34] Florian Marquardt, J. G. E. Harris, and S. M. Girvin. Dynamical multistability induced by radiation pressure in high-finesse micromechanical optical cavities. *Physical Review Letters*, 96(10):103901, 2006.
- [35] V.B. Braginsky, Y. I. Voronstov, and K. P. Thorne. Quantum nondemolition measurements. *Science*, 209:547–557, 1980.
- [36] Jay Gambetta, W. A. Braff, A. Wallraff, S. M. Girvin, and R. J. Schoelkopf. Protocols for optimal readout of qubits using a continuous quantum nondemolition measurement. *Physical Review A (Atomic, Molecular, and Optical Physics)*, 76(1):012325, 2007.
- [37] L. S. Levitov. The statistical theory of mesoscopic noise. In In Yu. Nazarov, editor, *Quantum Noise in Mesoscopic Systems*, pages 373–396, Amsterdam, 2003. Kluwer.
- [38] A. A. Clerk and D. Wahyu Utami. Using a qubit to measure photon-number statistics of a driven thermal oscillator. *Physical Review A (Atomic, Molecular, and Optical Physics)*, 75(4):042302, 2007.
- [39] T.M. Cover and J. A. Thomas. *Elements of Information Theory*. Wiley, New York, 1991.